

## Deliverable D2.1

### 5G-VINNI Solution facility sites High Level Design (HLD) - v1 Munich Facility Site annex (Release 4)

|   |   |
|---|---|
| Editor:                                   | Huawei  |
| Deliverable nature:                       | Report (R)  |
| Dissemination level:<br>(Confidentiality) | Public (PU)   |
| Contractual delivery date:                | N/A   |
| Actual delivery date:                     | 30 June 2021  |
| Suggested readers:                        | Example: Executives in entertainment companies and banks, investors |
| Version:                                  |   |
| Total number of pages:                    | 26  |
| Keywords:                                 | 5G, Solution Design, High Level Design                              |

---

#### ***Abstract***

Description of network services for each facility site. Includes configuration of Infrastructure, RAN, Core and MANO components and of the interconnections among them. Used as a reference for the orchestration and testing activities. Description of the cross-facility site services and interconnection requirements and configurations.

[End of abstract]

---



## Disclaimer

---

This document contains material, which is the copyright of certain 5G-VINNI consortium parties and may not be reproduced or copied without permission.

All 5G-VINNI consortium parties have agreed to full publication of this document.

The commercial use of any information contained in this document may require a license from the proprietor of that information.

Neither the 5G-VINNI consortium as a whole, nor a certain part of the 5G-VINNI consortium, warrant that the information contained in this document is capable of use, nor that use of the information is free from risk, accepting no liability for loss or damage suffered by any person using this information.

The EC flag in this document is owned by the European Commission and the 5G PPP logo is owned by the 5G PPP initiative. The use of the flag and the 5G PPP logo reflects that 5G-VINNI receives funding from the European Commission, integrated in its 5G PPP initiative. Apart from this, the European Commission or the 5G PPP initiative have no responsibility for the content.

*This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 815279.*

## Impressum

---

|   |  |
|---|--|
| <b>Full project title</b>                 | 5G Verticals Innovation Infrastructure   |
| <b>Project acronym</b>                    | 5G-VINNI   |
| <b>Number and title of work-package</b>   | WP2 5G-VINNI End-to-End Facility Implementation and Infrastructure Integration                           |
| <b>Number and title of task(s)</b>        | T2.1 Mapping of the Reference Architecture to Facility sites   |
| <b>Document title</b>                     | 5G-VINNI Solution facility sites High Level Design (HLD) – v1 – Munich Facility Site annex – (Release 4) |
| <b>Editor: Name, company</b>              | Huawei DE  |
| <b>Work-package leader: Name, company</b> | Terje Rød, Ericsson  |

## Copyright notice

© 2021 Participants in 5G-VINNI project

## List of authors

| Company | Author         | Contribution   |
|---------|----------------|--|
| HWDU    | Osama Abboud   | Established the doc, MEC details of the site, coordination |
| HWDU    | Xun Xiao       | Core network details, platform                             |
| HWDU    | Mohamed Gharba | RAN and radio details of the site                          |
| HWDU    | Artur Hecker   | MANO, NFV, SDN core network details, coordination          |

## Table of Contents

|  |    |
|--|----|
| List of authors.....                           | 3  |
| Table of Contents .....                        | 4  |
| List of figures .....                          | 6  |
| List of tables .....                           | 7  |
| Abbreviations .....                            | 8  |
| 1 Introduction.....                            | 9  |
| 1.1 Scope .....                                | 9  |
| 1.2 5G VINNI Facility.....                     | 9  |
| 1.3 Facility-site: Munich, Germany .....       | 10 |
| 1.3.1 Location details .....                   | 10 |
| 1.3.2 Vendors information .....                | 10 |
| 2 Facility-site deliverables .....             | 11 |
| 2.1 Facility-site use cases .....              | 11 |
| 2.2 Facility-site capabilities .....           | 11 |
| 2.3 Facility-site services.....                | 11 |
| 3 Mapping of global architecture from WP1..... | 12 |
| 4 Facility-site end-to-end design .....        | 15 |
| 4.1 Transport network.....                     | 15 |
| 4.2 5G RAN and Core.....                       | 15 |
| 4.2.1 RAN.....                                 | 15 |
| 4.2.2 Core Network .....                       | 16 |
| 4.2.3 RAN/Core Integration.....                | 16 |
| 4.3 MANO and NFVI .....                        | 17 |
| 4.3.1 NFVI .....                               | 17 |
| 4.3.2 MANO .....                               | 17 |
| 5 Facility-site solution design (HLD) .....    | 19 |
| 5.1 Security.....                              | 19 |
| 5.2 Transport Network .....                    | 19 |
| 5.3 NFVI .....                                 | 19 |
| 5.3.1 Hypervisor .....                         | 19 |
| 5.3.2 Computing .....                          | 19 |
| 5.3.3 Network.....                             | 19 |
| 5.3.4 Storage .....                            | 19 |
| 5.3.5 EMS.....                                 | 19 |
| 5.4 MANO.....                                  | 19 |
| 5.4.1 NFV Orchestrator.....                    | 19 |
| 5.4.2 VNF Manager.....                         | 20 |
| 5.4.3 VIM .....                                | 20 |
| 5.4.4 SDN .....                                | 20 |
| 5.4.5 EMS.....                                 | 20 |

|       |  |    |
|-------|--|----|
| 5.5   | Service Orchestration .....                                | 20 |
| 5.6   | 5G RAN and Core .....                                      | 20 |
| 5.6.1 | eNB .....  | 20 |
| 5.6.2 | Provisioning .....   | 21 |
| 5.6.3 | EMS .....  | 21 |
| 5.7   | MEC .....  | 21 |
| 5.7.1 | Architecture .....   | 22 |
| 5.7.2 | Applications .....   | 22 |
| 5.8   | Test Equipment .....                                       | 22 |
| 5.9   | Facility-site configuration (LLD) .....                    | 22 |
| 6     | Dimensioning and BOM .....                                 | 23 |
| 6.1   | gUE .....  | 23 |
| 6.2   | Transport Network .....                                    | 23 |
| 6.3   | MANO and NFVI .....  | 23 |
| 6.4   | 5G RAN and Core .....                                      | 23 |
| 6.4.1 | eNB .....  | 23 |
| 6.4.2 | gNB .....  | 23 |
| 6.4.3 | MME .....  | 23 |
| 6.4.4 | SGW/PGW .....  | 24 |
| 6.4.5 | PCRF .....   | 24 |
| 6.4.6 | HSS & Subscriber Database .....                            | 24 |
| 6.4.7 | Provisioning System .....                                  | 24 |
| 6.4.8 | EMS .....  | 24 |
| 6.5   | Test Equipment .....                                       | 24 |
| 7     | Cross-Facility-sites end-to-end design .....               | 25 |
| 7.1   | Facility-sites <this site name> and <2nd site name> .....  | 25 |
| 7.1.1 | Provided services .....                                    | 25 |
| 7.1.2 | Interconnection requirements .....                         | 25 |
| 7.2   | Facilities-site <this site name> and <3rd site name> ..... | 25 |
| 7.2.1 | Provided services .....                                    | 25 |
| 7.2.2 | Interconnection requirements .....                         | 25 |
| 8     | API .....  | 26 |
| 8.1   | Orchestration API .....                                    | 26 |
| 8.2   | ENM API .....  | 26 |

**List of figures**

Figure 1 5G-VINNI Facility..... 9

Figure 2 5G Munich Facility site ..... 15

Figure 3 5G Munich setup/configuration ..... 16

Figure 4 RAN/Core Integration..... 17

Figure 5 A GUI developed by HWDU Munich to operate NFVI ..... 18

Figure 6 Network Control GUI running a virtual network of several thousands nodes..... 21

**List of tables**

Table 1 Facility-site details ..... 10

Table 2 Location address..... 10

Table 3 Location vendors details..... 10

Table 4 WP1/WP2 architecture mapping 1..... 12

Table 5 WP1/WP2 architecture mapping 2..... 14

Table 6 WP1/WP2 architecture mapping 3..... 14

Table 7 VNF vSGSN-MME vBOM ..... 23

## Abbreviations

|          |  |
|----------|--|
| 5G       | Fifth Generation (mobile/cellular networks)                    |
| 5G-VINNI | 5G Verticals INNOvation Infrastructure                         |
| HLD      | High Level Design  |
| LLD      | Low Level Design   |
| MANO     | Management and Orchestration                                   |
| NFV      | Network Functions Virtualization                               |
| VNF      | Virtual Network Function                                       |
| NFVI     | Network Functions Virtualization Infrastructure                |
| VIM      | Virtualized Infrastructure Manager                             |
| RAN      | Radio Access Network   |
| eNB      | evolved NodeB  |
| gNB      | gNodeB (g=Next Generation)                                     |
| gUE      | g User Equipment (g=Next Generation)                           |
| SGSN     | Serving GPRS Support Node (GPRS= General Packet Radio Service) |
| MME      | Mobility Management Entity                                     |
| SGW/PGW  | Serving Gateway / PDN Gateway (PDN= Packet Data Network)       |
| PCRF     | Policy and Charging Rules Function                             |
| HSS      | Home Subscriber Server   |
| EMS      | Element Management System                                      |
| MEC      | Mobile Edge Computing, Multi-access Edge Computing             |



# 1 Introduction

## 1.1 Scope

This document is description of network services for 5G-VINNI specific facility site. Includes configuration of Infrastructure, RAN, Core and MANO components and of the interconnections among them. Used as a reference for the orchestration and testing activities. Description of the cross-facility site services and interconnection requirements and configurations.

## 1.2 5G VINNI Facility




Figure 1 5G-VINNI Facility

### 1.3 Facility-site: Munich, Germany

**Table 1 Facility-site details**

| Facility-site    |                            |
|------------------|----------------------------|
| Type             | Experimental Facility Site |
| Locations        | Munich                     |
| Provider         | HWDU                       |
| 5G-VINNI Release | <i>Release 2</i>           |

*Note: "Facility-site" has the same meaning as "Site". Within one site can be one or more "Locations".*

#### 1.3.1 Location details

**Table 2 Location address**

| Address               |                                  |
|-----------------------|----------------------------------|
| City, Street          | <i>Riesstr. 25, 80992 Munich</i> |
| Building, Room number | <i>Building C</i>                |

#### 1.3.2 Vendors information

**Table 3 Location vendors details**

| Domain  | Vendor      |
|---------|-------------|
| 5G RAN  | <i>HWDU</i> |
| 5G Core | <i>HWDU</i> |
| NFVI    | <i>HWDU</i> |

## 2 Facility-site deliverables

### 2.1 Facility-site use cases

The use case in the focus of investigation of the 5G-VINNI experimental facility site in Munich is:

- eHealth use-case: This use case is based on equipping an ambulance car with 5G capabilities. The ambulance car is considered as the first room of a hospital. When the hospital is far away the diagnosis and treatment in prior to arrival helps to increase patient safety. We provide a Virtual presence of medical expert (located in the hospital). Our target in the Test is to provide 5G based data transfer between moving point of care (ambulance= first responder) and university hospital (medical expert) facilitating bi-directional data transmission for ultrasound, audio and video source.

### 2.2 Facility-site capabilities

1. 5G Radio Access Network (RAN) at one site, with two sectors, each having
  - a. Carrier frequency: 3.4 GHz
  - b. Bandwidth: 40 MHz
  - c. Transmission power: 5 W
  - d. Antennas: up to 8
2. 5G Mobile Terminals (MT)
  - a. 5G Core network: HW/SW platform with 5G Core Network on top
3. Hardware: in-house platform comprising of several dozen powerful servers representing a data centre.
4. Software: software networks testbed, comprising extended network emulators (e.g., cluster Mininet with Docker extensions), controllers (e.g., Floodlight), open-source and proprietary switch implementations.
5. Orchestration platform for scenarios relevant to virtualization.
6. 5G Core network supporting functional split – SDN – NFV Orchestration
  - a. Distributed data centres for mobile edge computing use cases

### 2.3 Facility-site services

#### RAN

- Testbed can deploy virtual networks with different topologies as needed including transport networks
- Virtual networks can be deployed across a server cluster.
- Nodes as compute containers (e.g. Docker) that run distributed agent programs to test/evaluate various proposed protocols.

#### Radio

- URLLC Service, eMBB

### 3 Mapping of global architecture from WP1

*Note: the recommendations seem not yet defined by WP1 and therefore they will not be listed here. Once the recommendations are finalized, they will be listed here.*

Domains: 5G Radio and Core

**Table 4 WP1/WP2 architecture mapping 1**

| Number | WP1 recommendation                           | WP2 Implementation  | Note |
|--------|--|---|------|
| 1      | <b>RAN Functionality</b>                     | SA<br><i>Throughput DL: 30.8 Mbps , UL: 54 Mbps</i><br><i>Latency: DL/UL: 0.5ms</i><br><i>Reliability: 99.999 %</i><br><i>Carrier Frequency (C-Band) [3.41, 3.43, 3.45, 3.47, 3.49, 3.51, 3.53, 3.55, 3.57, 3.59] GHz</i> | 1    |
| 2      | <b>LTE – NR Dual Connectivity</b>            | N.A.  | 2    |
| 3      | <b>Mobility</b>                              | N.A.  | 3    |
| 4      | <b>Uplink/downlink Decoupling</b>            | N.A.<br><i>Not all sites will support this.</i>   |      |
| 5      | <b>LTE-NR Aggregation</b>                    | N.A.<br><i>Not all Sites require LTE-NR aggregation to prove the key KPI of 5G.</i>   |      |
| 6      | <b>Multiple Input Multiple Output (MIMO)</b> | <i>gNB: can support 8 Antennas, UE can support 4 Antennas.</i>  |      |
| 7      | <b>Numerology support</b>                    | <i>Flexible numerology is supported by the Munich site</i>  |      |

|    |  |                                       |  |
|----|--|---------------------------------------|--|
| 8  | <b>Carrier Bandwidths NR</b>                                     | <i>20 MHz: UU<br/>40MHz: Sidelink</i> |  |
| 9  | <b>Modulation</b>  | <i>AMC</i>                            |  |
| 10 | <b>Network slice aware RAN</b>                                   | <i>RAN Slicing</i>                    |  |
| 11 | <b>RAN integration with NR standalone (SA) Core architecture</b> | <i>Ok</i>                             |  |
| 12 | <b>NR QoS Framework</b>  |                                       |  |
| 13 | <b>5G Fixed Wireless Access (FWA)</b>                            |                                       |  |
| 14 | <b>Dynamic spectrum sharing</b>                                  |                                       |  |
| 15 | <b>Energy Efficiency</b>   |                                       |  |
| 16 | <b>Satellite backhaul</b>  |                                       |  |
| 17 | <b>Operational efficiency</b>                                    |                                       |  |
| 18 | <b>Public safety</b>   |                                       |  |
| 19 | <b>cMTC and mMTC</b>   |                                       |  |
| 20 | <b>NR Side Link</b>  | <i>Sidelink</i>                       |  |
| 21 | <b>Network Slice aware RAN</b>                                   |                                       |  |
| 22 | <b>Decomposition of RAN</b>                                      |                                       |  |

Domains: MANO and NFVI

**Table 5 WP1/WP2 architecture mapping 2**

| Number | WP1 recommendation | WP2 Implementation                     | Note |
|--------|--------------------|--|------|
| 1      | MANO and NFVI      | In-house MANO and NFVI system in Rel.1 |      |
| 2      |                    |  |      |
| ..     |                    |  |      |

Domain: Service Orchestration (not applicable)

**Table 6 WP1/WP2 architecture mapping 3**

| Number | WP1 recommendation    | WP2 Implementation | Note |
|--------|-----------------------|--------------------|------|
| 1      | Service Orchestration | N.A.               |      |
| 2      |                       |                    |      |
| ..     |                       |                    |      |

## 4 Facility-site end-to-end design

### 4.1 Transport network

*Not applicable as this is an experimental facility site and the whole site is in one building*

### 4.2 5G RAN and Core

#### 4.2.1 RAN

The RAN geographical structure are depicted in the map of Figure 2. The RAN site is located in the Riesstrasse 25 in Munich Germany.




Figure 2 5G Munich Facility site

The setup of the RAN site and the interconnections are depicted in Figure 3.




Figure 3 5G Munich setup/configuration

#### 4.2.2 Core Network

Physically, the core network platform consists of a dedicated server farm composed of COTS servers in racks, patch panels and DC switches.

- **CPU and Memory:** Every COTS server has 48 *Intel(R) Xeon(R) E5-2697 v2 @ 2.70GHz* CPUs and each CPU has 12 cores. Every server has 80GB RAM.
- **Ethernet:** Every server has 8 Ethernet ports.
- **Networking:** All servers are interconnected with a maximum bandwidth of 10Gb/s.

#### 4.2.3 RAN/Core Integration

The RAN and Core network have been integrated to allow for end to end testing. The RAN acts as a transport network of frames sent from the UE toward the NFs running in the core. The Base band running at the both ends will use the latest technique in order to achieve the KPIs. the UE is currently



fitted into a car in order to test urban V2X scenarios. The Core network runs the applications for the V2X scenario and will be able to execute the test cases.




Figure 4 RAN/Core Integration

## 4.3 MANO and NFVI

### 4.3.1 NFVI

Docker<sup>1</sup> container and Mininet<sup>2</sup> are utilized together to realize our NFVI multi-host platform on top of our hardware installation. Docker containers provide a virtualized environment, where different NFs can share the same hardware resource from the server machine isolated from each other.

Mininet provides software-defined networking capability to customize the interconnectivity of the virtualized NFs running in Docker containers through Open Virtual Switch (OVS)<sup>3</sup>. Mininet also provides capability to connect to one or multiple software-defined network controllers. Network control application logic can operate the network via the interfaces provided by the controller.

At HWDU experimental facility site, we use a multiple-host capable, mobility-supporting extended Mininet testbed. In this testbed, nodes are Docker containers with an OVS instance inside (as opposed to OVS, as in standard Mininet). Besides, such nodes can be deployed across different physical hosts; our system guarantees that regardless of the virtual node to physical machine assignment, the desired virtual topology constraints are always respected. Finally, nodes can be reattached within the network, therefore emulating mobility events.

### 4.3.2 MANO


At HWDU experimental facility site, we do not have a formal MANO system in the sense of ETSI NFV definition.

However, we have full control over both the physical platform and the deployed virtual network, including runtime control. We use a special Network Control Graphical User Interface (GUI) developed in house for these purposes.

<sup>1</sup> <https://www.docker.com/>

<sup>2</sup> <http://mininet.org/>

<sup>3</sup> <https://www.openvswitch.org/>



**Figure 5 A GUI developed by HWDU Munich to operate NFVI**

This GUI allows:

- Virtual network design (topology, number and types of nodes, addressing, assignment to physical hosts)
- Virtual network deployment (start and stop)
- Virtual network runtime control, including topology control (link up/down, node reattachment, node up/down) and running service control (like remote shell capability into the virtual nodes and the changes to the virtual link).

## 5 Facility-site solution design (HLD)

### 5.1 Security

Not applicable.

### 5.2 Transport Network

The transport network will be based on simple Ethernet capability. Reason being that the base station and the core network are found within the same building.

### 5.3 NFVI

#### 5.3.1 Hypervisor

We use Ubuntu 12 LTS or 14 LTS on our platform servers. The hypervisor therefore is the Linux kernel, and, in principle, any available kernel hypervisor could be used (kvm/qemu, xen, lxc). We mostly use container-based virtualization and Docker containers, which rely on ns and cg capabilities of the Linux kernel, i.e. namespaces, control groups, chroot, etc.

#### 5.3.2 Computing

Linux/Docker is used as the computing environment, where NF application are encapsulated into a Docker container corresponding to its resource requirement.

#### 5.3.3 Network

Mininet is used to provide programmable networking capability, where VNF applications running in individual Docker containers can be interconnected. Networking will be operated by control applications running over network controllers.

#### 5.3.4 Storage

Storage resource is allocated with the configuration of the Docker container that hosts the NF application. Such a storage configuration can be dynamically changed if more storage capability is needed.

#### 5.3.5 EMS

Realized through the mentioned graphical network control GUI (see section 4.3.2).

### 5.4 MANO

#### 5.4.1 NFV Orchestrator

The network control GUI presented above serves as a simple yet efficient orchestrator used for deployment and removal of both the whole virtual network and of all individual elements thereof (nodes or links).

Previously at HWDU, we have researched and implemented highly efficient placement algorithms (VNE solutions based on MIP solvers with particular problem and optimization formulations), however we currently do not use them in our testbed. These are available and could be integrated and tested, if required.

Since our testbed is oriented towards research and testing of different mechanisms, the lifecycle management is following the experiment logic: a new experiment is deployed as a virtual network of

particular VNFs instantiated depending on their realization; a scenario is initiated automatically after the deployment; the results/measurements are gathered as part of the scenario during its execution; finally, the network is stopped and removed after the experiment.

#### 5.4.2 VNF Manager

In our system, the VNFs can be either:

Compiled native software, e.g., access controllers, traffic shapers, NAT, gateways, proxies, accelerators, etc. on the data plane (to instantiate a UPF of a particular kind), packaged as specially crafted Docker container images. These images interface with our runtime coordination system, which therefore can enforce specific start and stop behavior of services and interact with the installed software e.g., over (interactive or scripted) remote shell.

Java control applications, packaged as compiled Java classes, to be installed and run on top of the SDN controller system, i.e. FloodLight with our 5G Layer.

Combinations of the above, i.e. SDN Control Applications and particular software within different nodes. This mode can be used to implement distributed NF realizations.

In practice, all three are used. The maintenance of the images, Java classes and the hybrid applications is done by a build system.

#### 5.4.3 VIM

The virtual network control GUI is used as a VIM, as it is possible to interact with the running VNFs from the GUI. For specific interactions, we use GUI exports, which become available as graphical menu properties of elements. For general interactions, a remote shell can be opened to any node.

#### 5.4.4 SDN

The virtual network is using OpenVSwitch (OVS) as reference implementation of a (virtual) OpenFlow SDN switch. Although our testbed can use different SDN controllers, we currently rely on FloodLight.

Pox, Ryi, OpenDayLight and ONOS could be used alternatively, if required.

On top of FloodLight we are using a particular “5G Layer”, which includes common routines for processing and dispatching 5G events to different 5G NFs.

#### 5.4.5 EMS

In our experimental facility site, we do not use any EMS for MANO elements per se.

### 5.5 Service Orchestration

Not applicable.

### 5.6 5G RAN and Core

#### 5.6.1 eNB

No 4G equipment is used in the Munich experimental facility site.

- gNB
- Carrier Frequency: 3.4 GHz
- Bandwidth: 20 MHz
- Maximum UEs: 3
- Antenna gain: 12dBi
- TX power per antenna: 28dBm

## 5.6.2 Provisioning

As it is an experimental facility site, we do not use formal provisioning at the Munich experimental facility site. However, virtual networks can be scaled up and down, including in runtime.

## 5.6.3 EMS

Realized through the mentioned graphical network control GUI (see section 4.3.2).

We are implementing (Rel0 and Rel1) a home-made GUI to interact with the virtual network at the backend servers. The GUI considers management and operation tasks to control the virtual networks deployed at the backend servers. The GUI utilizes a 3rd-party network graph-tool as a visualization widget to visualize the virtual networks running at the backend servers. The network graph-tool of the GUI is also used when a new virtual network is designed including different types of network nodes, links and their topology before the virtual topology is deployed to the backend servers. The GUI also supports interactions with the network nodes and links such as node/link on and off, etc.. Each network node is implemented as a docker container integrated with OVS, every network link is a virtual link either intra-host or inter-host linux virtual link. Interactions with network nodes are done by RPC requests from the frontend to the backend, where a proxy server is responsible to distribute an RPC to corresponding network nodes




Figure 6 Network Control GUI running a virtual network of several thousands nodes

## 5.7 MEC

As this is experimental facility site, no ETSI MEC implementation is available. However, it is possible to deploy Docker containers and virtualization at the edge of network in order to provide low latency communication.

**5.7.1 Architecture****5.7.2 Applications****5.8 Test Equipment**

Not applicable as this is an experimental facility site.

**5.9 Facility-site configuration (LLD)**

Not applicable as this is an experimental facility site.

## 6 Dimensioning and BOM

Not applicable as this is an experimental facility site.

### 6.1 gUE

### 6.2 Transport Network

### 6.3 MANO and NFVI

### 6.4 5G RAN and Core

#### 6.4.1 eNB

#### 6.4.2 gNB

#### 6.4.3 MME

Table 7 VNF vSGSN-MME vBOM

| VNF Name      | VM Type | AFFINITY RULES<br>- 'INTRA VNF' | AFFINITY RULES<br>- 'INTER VNF' | VM Workload<br>type | No. of VMs per<br>type | No. of vCPU per<br>VM | RAM (GB) per<br>VM | Storage (GB)<br>per VM |
|---------------|---------|---------------------------------|---------------------------------|---------------------|------------------------|-----------------------|--------------------|------------------------|
| vSGSN-<br>MME | NCB     |                                 |                                 |                     |                        |                       |                    |                        |
|               | FSB     |                                 |                                 |                     |                        |                       |                    |                        |
|               | GEP     |                                 |                                 |                     |                        |                       |                    |                        |
|               | LC      |                                 |                                 |                     |                        |                       |                    |                        |

**6.4.4 SGW/PGW****6.4.5 PCRF****6.4.6 HSS & Subscriber Database****6.4.7 Provisioning System****6.4.8 EMS****6.5 Test Equipment**

Not applicable as this is an experimental facility site.



## **7 Cross-Facility-sites end-to-end design**

Not applicable as this is an experimental facility site.

### **7.1 Facility-sites <this site name> and <2nd site name>**

#### **7.1.1 Provided services**

#### **7.1.2 Interconnection requirements**

### **7.2 Facilities-site <this site name> and <3rd site name>**

#### **7.2.1 Provided services**

#### **7.2.2 Interconnection requirements**

## **8 API**

Not applicable as this is an experimental facility site.

### **8.1 Orchestration API**

### **8.2 ENM API**

[end of document]